



A-60 ClovaTex

Non-Skid Additive

General Properties

A polypropylene non-skid additive that is easily added to most types of paint to provide a durable, skid resistant finish. Once added, the beads remain suspended and can be sprayed with most airless and conventional spray equipment.

Recommended Uses

For use in interior or exterior paints to create a safer, non-skid surface for foot traffic.

Product Information

GENERIC TYPE	Polypropylene Bead
COLOR	Translucent
AVERAGE VOLUME SOLIDS	100%

FLASH POINT	N/A
SHELF LIFE	Indefinite
VISCOSITY	No effect

Warning

Before mixing or using ClovaTex, read and follow all label directions appropriate to the coating being used.

Limitations

ClovaTex is a fine particle sized aggregate which will improve skid or slip resistance for most applications. It is not intended for use around hazardous equipment, or in industrial environments where a more aggressive aggregate should be used.

Mixing Instructions

Stir In Method: Mix 4 oz. of ClovaTex to a gallon of catalyzed Cloverdale Urethane or Epoxy paint after the appropriate induction time. Reduce to application viscosity as required. Spray*, brush or roll using standard equipment. * a slightly larger orifice may be required.

Broadcast Method: Properly catalyze and induce Cloverdale Urethane or Epoxy coatings. Apply a tack coat to the non-skid area. Apply a dusting of ClovaTex using a perforated apparatus at a rate of approximately 1 oz./100ft². * The amount of ClovaTex may be varied to give higher or lower degree of texture.

Safety Precautions

A NIOSH/MSHA approved mask for particulate matter is recommended when handling ClovaTex.

Storage and Handling

FLASH POINT	N/A
PRODUCT WEIGHT	7.5 lbs/gal (container extra)
STORAGE	Dry location. See your Cloverdale Paint Representative.
PACKAGE SIZE	8 oz. Bags

Warranty Disclaimer

Cloverdale Paint manufactures quality products. In the event that this product is defective or in any way unsuitable for the application for which it is sold, Cloverdale Paint Inc. will replace the product free of charge. The warranty provided by this data sheet is the only warranty or guarantee of quality made in respect of this product by Cloverdale Paint Inc. By purchasing this product the customer accepts this warranty in lieu of all others, and waives all claims to any other remedy arising from any warranty or guarantee of quality, whether such warranty or guarantee of quality was made expressly to the customer or implied by any applicable law.

Check for recent amendments to this data sheet at www.cloverdalepaint.com



Cloverdale Paint Inc.

6950 King George Highway, Surrey, British Columbia, Canada V3W 4Z1
Web Site: www.cloverdalepaint.com Email: helpdesk@cloverdalepaint.com
Phone: 604 596 6261 Fax: 604 597 2677